

Technical features

Armchair for conference halls, auditoriums and multi-purpose spaces.

Installation on horizontal and inclined floors or on steps, in straight or curved rows (minimum radius 8 m.).

Variable centre to centre distance from 53 to 60 cm.

Seat and backrest

Seat and backrest with plywood internal structure, fire-retardant and crushproof expanded polyurethane padding.

Gravity tip-up seat, with steel rotation pins.

Inclined and shaped backrest that ensure a better comfort thanks to the curved internal structure.

Covered with fabric, eco-leather or leather.

Sides

Fully upholstered sides with plywood internal structure with aluminium block for the insertion of rotation and seat support pins.

Fabric, leather or eco-leather covering.

Right sides are also available with stratified HPL tip-up writing tablet with black finish and anti-panic movement, which folds away into the side.

Floor fixing feet in steel profile painted with epoxy-polyester powder in RAL 9005 semi-matt, semi-matt silver, embossed bronze and embossed graphite scratchproof finishes.

Accessories

Tip-up writing table on single base mod T200.

Stratified HPL tip-up foldaway writing tablet with anti-panic movement.

Seat numbering and row identification element.

Electric power supply provision (socket on demand).

Optional system allowing armchairs to be moved away, on castors, when not in use (for armchairs in straight rows).