

Mura

Gino Gamberini

Technical features

Armchair for conference halls and auditoriums.

Typologies

Mura is available in the standard version and VIP version with higher backrest (of 15 cm.), also the side is available in two thicknesses (29 and 45 cm.).

All versions are available with base plates to the floor for each seat or on beam of 2-3 places connected in rows.

Installation on horizontal and sloping floors, on steps, in straight or curved rows (with double side).

Seat and backrest

Seat structure in tubular steel, padding in flame-retardant, non-deformable polyurethane foam.

Backrest available in two heights with plywood internal structure, padding in flame-retardant, non-deformable expanded polyurethane.

Armchair equipped with a gravity system which releases and tips up the seat with a shock absorption movement. At the same time the seat drops and uprights, reducing the volume of the armchair and increasing the available space between rows with a considerable advantage for the audience access/exit and for the cleaning and maintenance operations.

The armchair is equipped with a sliding mechanism of seat and backrest that provides a variable layout: the user can adopt a more erected or relaxing position for better comfort.

Side

Side with thickness of 29 or 45 cm., has internal bearing structure in tubular steel painted with a rust-proofing treatment hidden into a plywood box with padding in flame-retardant, expanded polyurethane, armrest fully upholstered and covered with fabric, leather or eco-leather.

The arm side is foreseen for floor-fixing, the anchoring foot is hidden under a steel foot cover collar painted in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite.

The 45 cm. thick side can be fitted with stratified HPL anti-panic writing tablet that folds away into the side.

The seat rotation and backrest sliding mechanisms are fixed directly internally on the frame in tubular steel and are in self-lubricating Delrin.

Also available the beam (2 or 3 places) in tubular steel square section, painted with scratchproof epoxy powder paint in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite finish, with floor-mounted feet or anti-tilt feet with registers.

In the beam-mounted version, the sides have the same characteristics but are available with one height side panels resting on the beam (with the exception of the sides starting row which can also reach the ground).

Accessories

Stratified HPL tip-up writing tablet with anti-panic movement (for 45 cm. thick side).

Seat and row identification elements.

Electrification provision (socket on demand).

Optional system allowing armchairs to be moved away on wheels when unused (for floor-fixing armchairs in straight rows).